

IKA

designed for scientists



S 25 N - 25 F Dispersing tool

/// Data Sheet

Suitable for dispersing instrument T 25 digital

Working range: 100 - 2.000 ml

Stator diameter: 25 mm

Immersion depth: 40 - 165 mm

Materials in contact with medium: PTFE, AISI 316L

Suitable for solvents

Max. temperature: 180 °C

Sterilization methods: all methods

www.imlab.eu

info@imlab.be - Tél. : +32 (0)16 73 55 72

imLab

www.imlab.eu

info@imlab.fr - Tél. : +33 (0)3 20 55 19 11

Imlab sprl - Oude Vijvers, 1
3370 Boutersem - Belgique

Imlab sarl - Centre d'Affaires de l'Horlogerie
48 rue des Canoniers - 59000 Lille - France



designed for scientists

Technical Data

Volume range (H ₂ O) [l]	0.1 - 2
Stator diameter [mm]	25
Rotor diameter [mm]	18
Gap between rotor and stator [mm]	0.5
allowable Speed max. [rpm]	25000
Circumferential speed max. [m/s]	23.6
Immersion depth [mm]	40 - 165
Shaft length [mm]	194
Material in contact with medium	PTFE, AISI 316L
pH range	2 - 13
Suitable for solvents	yes
Suitable for abrasive substances	yes
Working temperature max. [°C]	180
Sterilization methods	all methods
Ultimate fineness, suspensions [µm]	5 - 25
Ultimate fineness, emulsions [µm]	1 - 5

www.imlab.eu

info@imlab.be - Tél. : +32 (0)16 73 55 72



www.imlab.eu

info@imlab.fr - Tél. : +33 (0)3 20 55 19 11

Imlab sprl - Oude Vijvers, 1
3370 Boutersem - Belgique

Imlab sarl - Centre d'Affaires de l'Horlogerie
48 rue des Canoniers - 59000 Lille - France